

Material Safety Data Sheet Cover-Sheet – This page provides additional New Zealand specific information for this product and must be read in conjunction with the Safety Data Sheet (SDS) attached

Product Name: GC Fuji LINING LC Paste Pak Paste A & B

Manufacturer: GC Corporation

SDS Expiry: 3 September 2025

Supplier Details: Henry Schein New Zealand

23 William Pickering Drive, Albany

PO Box 101 140, North Shore, Auckland 0745

Ph. 0800 808 855

www.henryschein.co.nz

Emergency Contacts: Poisons/Hazardous Chemical Info Centre –

0800POISON/0800764766 (24 Hours)
Phone 111 for Fire, Ambulance or Police

HSNO Class/Category: 6 / 8

HSNO Group Standard: Dental Products Subsidiary Hazard Group Standard 2017

HSR002558

Statements/Pictograms: As per attached Safety Data Sheet (SDS)

Date Prepared: This coversheet was prepared on 17 September 2020

This SDS coversheet has been produced by Henry Schein NZ and has been prepared in accordance with NZ EPA advice on making overseas SDS compliant to HSNO Act. The above information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith, no warranty is implied with respect to the quality or the specifications of the product. Users must satisfy that the product is entirely suitable for their purpose. The SDS and this coversheet may be revised from time to time, please ensure you have a current copy.





Printing date 03.09.2020 Version number 2 Revision: 03.09.2020

1 Identification of the substance or mixture and of the supplier

- · Product identifier
- · Trade name: GC Fuji LINING LC Paste Pak Paste A
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxillary for dental technology
- · Details of the supplier of the safety data sheet

Henry Schein Dental 23 William Pickering Drive, Albany Auckland 0632, NEW ZEALAND

PO Box 101140, NSMC Auckland 0745, NEW ZEALAND

Free Phone: 0800 808 855

- · Further information obtainable from: Regulatory affairs
- · Emergency telephone number: 0800 764 766 (National Poisons Centre)

2 Hazards identification

· Classification of the substance or mixture

Acute Tox. 5 H333 May be harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Exemptions

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

· Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labelling:

2-hydroxyethyl metacrylate 6-tert-butyl-2,4-xylenol

Urethane Dimethacrylate (UDMA)

· Hazard statements

May be harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

(Contd. on page 2)

Printing date 03.09.2020 Version number 2 Revision: 03.09.2020

Trade name: GC Fuji LINING LC Paste Pak Paste A

(Contd. of page 1)

May cause an allergic skin reaction.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapours/spray.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves / eye protection / face protection.

IF INHALED: Call a POISON CENTER/doctor if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

3 Composition/Information on ingredients

- · Chemical characterisation: Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous compone	ents:	
CAS: 868-77-9 EINECS: 212-782-2	2-hydroxyethyl metacrylate Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	10-<25%
CAS: 1830-78-0 EINECS: 217-388-4	2-Hydroxy-1,3 dimethacryloxypropane Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	5-<10%
CAS: 72869-86-4 EINECS: 276-957-5	Urethane Dimethacrylate (UDMA) Skin Sens. 1, H317	5-<10%
CAS: 1879-09-0 EINECS: 217-533-1	6-tert-butyl-2,4-xylenol Acute Tox. 2, H310; Acute Tox. 3, H331; STOT RE 2, H373; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Aquatic Acute 2, H401	0.1-<0.2%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

After eye contact:

Protect unharmed eye.

Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)

Printing date 03.09.2020 Version number 2 Revision: 03.09.2020

Trade name: GC Fuji LINING LC Paste Pak Paste A

(Contd. of page 2)

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed Allergic reactions
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

- · Advice for firefighters
- · **Protective equipment:** Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Avoid contact with the eyes and skin.

Wear protective clothing.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to penetrate the ground/soil.

In case of seepage into the ground inform responsible authorities.

· Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

Information about fire - and explosion protection: No special measures required.

(Contd. on page 4)

Printing date 03.09.2020 Version number 2 Revision: 03.09.2020

Trade name: GC Fuji LINING LC Paste Pak Paste A

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in unopened original receptacles.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: None.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

1879-09-0 6-tert-butyl-2,4-xylenol

Inhalative | DNEL inhalation | 0.14 mg/m3 (man)

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

- · Respiratory protection: Suitable respiratory protective device recommended.
- · Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Printing date 03.09.2020 Version number 2 Revision: 03.09.2020

Trade name: GC Fuji LINING LC Paste Pak Paste A

(Contd. of page 4)

Physical and chemical properties	
Information on basic physical and chen	nical properties
General Information	
Appearance:	
Form:	Pasty
Colour:	Yellow
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: Undetermined.
Flash point:	97 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	Undetermined.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density:	Not determined.
•	$2,56 \text{ g/cm}^3$
	1,18g/ml
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Insoluble.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
VOC (EC)	$0.0 \ g/l$
Other information	No further relevant information available.

10 Stability and reactivity

- $\cdot \textit{Reactivity} \ \textit{No further relevant information available}.$
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 6)

Printing date 03.09.2020 Version number 2 Revision: 03.09.2020

Trade name: GC Fuji LINING LC Paste Pak Paste A

(Contd. of page 5)

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

· LD/LC5	· LD/LC50 values relevant for classification:		
72869-8	72869-86-4 Urethane Dimethacrylate (UDMA)		
Oral	LD50	>5,000 mg/kg (rat female) (OECD 401)	
1879-09	1879-09-0 6-tert-butyl-2,4-xylenol		
Oral	LD50	910 mg/kg (rat (f+m)) (OECD 401)	
Dermal	LD50	<200 mg/kg (rabbit) (OECD 402)	

- Primary irritant effect:
- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eve damage/irritation Irritating effect.
- · Respiratory or skin sensitisation Sensitisation possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

- · Repeated dose toxicity No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

12 Ecological information

- · Toxicity
- · Aquatic toxicity:

72869-86-4 Urethane Dimethacrylate (UDMA)

EC50/48h (static) >1.2 mg/l (daphnia magna) (OECD 202)

- · Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

NZ

Printing date 03.09.2020 Version number 2 Revision: 03.09.2020

Trade name: GC Fuji LINING LC Paste Pak Paste A

(Contd. of page 6)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number		
ADR, ADN, IMDG, IATA	not regulated	
UN proper shipping name		
ADR, ADN, IMDG, IATA	not regulated	
Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	not regulated	
Packing group		
ADR, IMDG, IATA	not regulated	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex II	of Marpol	
and the IBC Code	Not applicable.	

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

	· New Zealand Inventory of Chemicals		
65997-17-3	Glass, oxide, chemicals		
868-77-9	2-hydroxyethyl metacrylate		
	Urethane Dimethacrylate (UDMA)		
	2-Hydroxy-1,3 dimethacryloxypropane		
68909-20-6	Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica		
2530-85-0	3-trimethoxysilylpropyl methacrylate		
10287-53-3	ethyl 4-dimethylaminobenzoate		
1879-09-0	6-tert-butyl-2,4-xylenol		

[·] GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

(Contd. on page 8)

Printing date 03.09.2020 Version number 2 Revision: 03.09.2020

Trade name: GC Fuji LINING LC Paste Pak Paste A

(Contd. of page 7)

· Hazard pictograms



· Signal word Warning

· Hazard-determining components of labelling:

2-hydroxyethyl metacrylate

6-tert-butyl-2,4-xylenol

Urethane Dimethacrylate (UDMA)

· Hazard statements

May be harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapours/spray.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves / eye protection / face protection.

IF INHALED: Call a POISON CENTER/doctor if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

· Relevant phrases

H302 Harmful if swallowed.

H310 Fatal in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H401 Toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 9)

Printing date 03.09.2020 Version number 2 Revision: 03.09.2020

Trade name: GC Fuji LINING LC Paste Pak Paste A

(Contd. of page 8)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - oral - Category 4 Acute Tox. 2: Acute toxicity - dermal - Category 2 Acute Tox. 3: Acute toxicity - inhalation - Category 3 Acute Tox. 5: Acute toxicity - inhalation - Category 5 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Sources

- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)
- * Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.



Printing date 03.09.2020 Version number 2 Revision: 03.09.2020

1 Identification of the substance or mixture and of the supplier

- · Product identifier
- · Trade name: GC Fuji LINING LC Paste Pak Paste B
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxillary for dental technology
- · Details of the supplier of the safety data sheet

Henry Schein Dental 23 William Pickering Drive, Albany Auckland 0632, NEW ZEALAND

PO Box 101140, NSMC Auckland 0745, NEW ZEALAND

Free Phone: 0800 808 855

- · Further information obtainable from: Regulatory affairs
- · Emergency telephone number: 0800 764 766 (National Poisons Centre)

2 Hazards identification

· Classification of the substance or mixture

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Exemptions

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

· Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

2-hydroxyethyl metacrylate

Tartaric acid

· Hazard statements

Causes skin irritation.

Causes serious eye damage.

May cause an allergic skin reaction.

(Contd. on page 2)

Printing date 03.09.2020 Version number 2 Revision: 03.09.2020

Trade name: GC Fuji LINING LC Paste Pak Paste B

(Contd. of page 1)

· Precautionary statements

Contaminated work clothing should not be allowed out of the workplace.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/Information on ingredients

- · Chemical characterisation: Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous compone	ents:	
CAS: 868-77-9	2-hydroxyethyl metacrylate	25-<50%
EINECS: 212-782-2	Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	
CAS: 9003-01-4	Polyacrylic acid	25-<50%
	Eye Irrit. 2, H319	
	2-Hydroxy-1,3 dimethacryloxypropane	5-<10%
EINECS: 217-388-4	Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
CAS: 87-69-4	Tartaric acid	5-<10%
EINECS: 201-766-0	Eye Dam. 1, H318	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eye contact:

Protect unharmed eye.

Rinse opened eye for several minutes under running water.

If symptoms persist consult doctor.

Call a doctor immediately.

(Contd. on page 3)

Printing date 03.09.2020 Version number 2 Revision: 03.09.2020

Trade name: GC Fuji LINING LC Paste Pak Paste B

(Contd. of page 2)

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed Allergic reactions
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

- · Advice for firefighters
- · **Protective equipment:** Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Avoid contact with the eyes and skin.

Wear protective clothing.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

· Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling Avoid contact with the eyes and skin.
- · Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in unopened original receptacles.
- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.

(Contd. on page 4)

Printing date 03.09.2020 Version number 2 Revision: 03.09.2020

Trade name: GC Fuji LINING LC Paste Pak Paste B

(Contd. of page 3)

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

- · Respiratory protection: Suitable respiratory protective device recommended.
- · Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Pasty
Colour: Yellow
Odour: Characteristic
Odour threshold: Not determined.

· pH-value: Not determined.

(Contd. on page 5)

Printing date 03.09.2020 Version number 2 Revision: 03.09.2020

Trade name: GC Fuji LINING LC Paste Pak Paste B

	(Contd	of page
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range	: Undetermined.	
Flash point:	Not applicable.	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	Undetermined.	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapour pressure:	Not determined.	
Density:	Not determined.	
•	$2,56 \text{ g/cm}^3$	
	1,18g/ml	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Fully miscible.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Water:	26.8 %	
VOC (EC)	$0.0 \ g/l$	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

N7

Printing date 03.09.2020 Version number 2 Revision: 03.09.2020

Trade name: GC Fuji LINING LC Paste Pak Paste B

(Contd. of page 5)

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity
- · LD/LC50 values relevant for classification: No further relevant information available.
- · Primary irritant effect:
- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eye damage/irritation Strong irritant with the danger of severe eye injury.
- · Respiratory or skin sensitisation Sensitisation possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Corrosive

- · Repeated dose toxicity No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport information

- · UN-Number
- · ADR, ADN, IMDG, IATA

not regulated

(Contd. on page 7)

Printing date 03.09.2020 Version number 2 Revision: 03.09.2020

Trade name: GC Fuji LINING LC Paste Pak Paste B

		(Contd. of page
UN proper shipping name ADR, ADN, IMDG, IATA	not regulated	
Transport hazard class(es)		
ADR, ADN, IMDG, IATA Class	not regulated	
Packing group ADR, IMDG, IATA	not regulated	
Environmental hazards: Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex L and the IBC Code	I of Marpol Not applicable.	
UN "Model Regulation":	not regulated	

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · New Zealand Inventory of Chemicals

All ingredients are listed.

- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms





GHS05

GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

2-hydroxyethyl metacrylate

Tartaric acid

· Hazard statements

Causes skin irritation.

Causes serious eye damage.

May cause an allergic skin reaction.

· Precautionary statements

Contaminated work clothing should not be allowed out of the workplace.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

(Contd. on page 8)

Printing date 03.09.2020 Version number 2 Revision: 03.09.2020

Trade name: GC Fuji LINING LC Paste Pak Paste B

(Contd. of page 7)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

· Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

· Department issuing SDS: Regulatory affairs

· Contact: msds@gc.dental

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

·Sources

- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)

* Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.